

This listing of claims will replace all prior versions, and listings, of claims in the application.

### **Listing of Claims**

1. (Currently Amended) A exterior rear view mirror for a vehicle comprising:
  - a base for mounting on a vehicle body;
  - a housing pivotally mounted on the base for angular movement about a first pivot axis, ~~and a second pivot axis;~~
  - a reflective member mounted in the housing for reflecting an image, said reflective member pivotable about a second pivot axis;
  - an electric motor having an output shaft selectively operable to cause angular movement of the housing about the first pivot axis;
  - a controller adapted to control the electric motor to selectively drive the housing about the first pivot axis either at the first speed or at the second speed which is faster than the first speed, and
  - a counter for counting the number of revolutions of the electric motor and determining the angle to which the housing has been moved.
2. (Cancelled)
3. (Previously Presented) An exterior rear view mirror according to claim 1, wherein when said housing is moved from a deployed position to a parked position, the controller will command the electric motor to rotate the housing about the first pivot axis at a speed of 30 degrees per second, positioning said housing in a folded position adjacent the side of the vehicle.
4. (Previously Presented) An exterior rear view mirror according to claim 3, wherein when the housing is to be returned to the deployed position from the parked position, the controller will command the electric motor to rotate the housing about the first pivot axis from the deployed position to the parked position, and the controller will

command the electric motor to rotate the same number of revolutions compared to when the housing was moved from the deployed position to the parked position, thereby moving the housing to the deployed position.

5. (Previously Presented) An exterior rear view mirror according to claim 1, wherein the reflective member further comprises a prism, and when the housing is tilted on the second axis, a driver of the vehicle will see a reflected image on the prism.

6. (Previously Presented) An exterior rear view mirror according to claim 1, wherein the second speed is at least five times as fast as the first speed.

7-15. (Cancelled)

16. (Previously Presented) An exterior rear view mirror for a vehicle comprising:  
a base for mounting on a vehicle body;  
a housing pivotally mounted on said base for angular movement about a first pivot axis;  
a reflective member pivotally mounted in said housing for angular movement about a second pivot axis;  
an electric motor contained in said housing, said electric motor having an output shaft selectively operable to cause the angular movement of said housing about said first pivot axis at a first discrete speed and at a second discrete speed; and  
a controller adapted to control the electric motor to selectively drive the housing about the first pivot axis either at a first speed or a second speed which is faster than the first speed; and  
a counter for counting the number of revolutions of the electric motor.

17. (Previously Presented) The exterior rear view mirror of claim 16 wherein the housing is moved from a deployed position to a parked position, the controller will command the electric motor to rotate the housing about the first pivot axis, positioning said housing in a folded position adjacent the side of the vehicle, the counter will count the number of revolutions performed by the electric motor.

18. (Previously Presented) The exterior rear view mirror according to claim 18 wherein when the housing is to be returned to the deployed position from the parked position, the controller will command the electric motor to rotate the housing about the first pivot axis from the parked position to the deployed position, and the controller will command the electric motor to rotate the same number of revolutions compared to when the housing was moved from the deployed position to the park position.

19. (Previously Presented) The exterior rear view mirror assembly of claim 16 wherein the reflective member further comprises a prism, and when said reflective member moved from said first position to said second position, a driver of a vehicle will see a reflected image on the prism.

20. (Allowed) An exterior rear view mirror for a vehicle comprising:  
a base for mounting on a vehicle body;  
a housing pivotally mounted on said base for angular movement about a first pivot axis;  
at least one rib integrally formed within the interior of said housing;  
a carrier contained within said housing and pivotally mounted to said at least one rib for pivoting about a second axis;  
a reflective member mounted on said carrier;  
a mounting member connected to said at least one rib and contained within said housing;  
an electric motor mounted on said mounting member, said electric motor having an output shaft selectively operable to cause angular movement of said housing about said first pivot axis at a first discrete speed and at a second discrete speed;  
a controller adapted to control the electric motor to selectively drive said housing about said first pivot axis either at a first discrete speed or at a second discrete speed which is faster than said first discrete speed; and  
wherein said exterior mirror further includes a counter for counting the number of revolutions of said electric motor.

21. (Allowed) The exterior mirror of claim 20, wherein said mirror carrier further includes at least one bracket journalled on a shaft, said shaft being mounted on said at least one rib, and forming said second pivot axis.

22. (Allowed) The exterior mirror of claim 20, wherein when said housing is moved from a deployed position to a parked position, the controller will command the electric motor to rotate the housing about the first pivot axis positioning said housing in a folded position adjacent the side of the vehicle against a stop, and the counter will count the number of revolutions performed by the motor.

23. (Allowed) The exterior rear view mirror of claim 22, wherein when the housing is to be returned to the deployed position from the parked position, the controller will command the electric motor to rotate the housing about the first pivot axis from the parked position to the deployed position, and the controller will command the electric motor to rotate the same number of revolutions compared to when the housing was moved from the deployed position to the parked position, thereby moving the housing to the deployed position.